Amendments to the Claims:

Please amend Claims 17, 18, 21, 22 and 23 and add new Claim 25 as set forth below:

1. (Previously Presented) An apparatus for measuring motion of a portion of the body of a patient in a magnetic field, comprising:

a cradle coupled around at least part of said portion of the body of said patient;

a length of wire coupled to said cradle and responsive to motion of said portion of the body of said patient; and

a voltage measuring device having an input coupled to said wire and an output representative of the motion of said portion of the body of said patient.

- 2. (Original) The apparatus of Claim 1, wherein said cradle is formed from a thin polycarbonate plastic strip.
- 3. (Original) The apparatus of Claim 1, wherein said length of wire is formed from a high resistance lead.
- 4. (Previously Presented) The apparatus of Claim 1, wherein said voltage measuring device comprises:
 - a Faraday shield forming an enclosure;

two RF filters mounted in said Faraday shield, each of said RF filters having an input coupled to said wire and an output;

a differential amplifier mounted within said enclosure and having two inputs and an output, each of said inputs coupled to a respective output of one of said two RF filters; Page 3 of 13

a gradient filter mounted within said enclosure and having an input and an output, said input of said gradient filter coupled to said output of said differential amplifier, and

September 7, 2007

Dkt. No. 73269/5

a transmitter mounted within said enclosure and having an input connected to said output of said gradient filter and an output representative of the motion of said portion of the body of said patient.

5. (Previously Presented) The apparatus of Claim 1, wherein said voltage measuring device comprises:

a Faraday shield forming an enclosure and coupled to said wire;

an RF filter mounted in said Faraday shield having an input coupled to said wire and an output;

a differential amplifier mounted in said enclosure and having two inputs and an output, one of said inputs coupled to said output of said RF filter and the other of said inputs connected to said Faraday shield;

a gradient filter mounted in said enclosure and having an input and an output, said input of said gradient filter coupled to said output of said differential amplifier, and

a transmitter mounted in said enclosure and having an input coupled to said output of said gradient filter and an output representative of the motion of said portion of the body of said patient.

6. (Previously Presented) An apparatus for measuring motion of a portion of the body of a patient in a magnetic field, comprising:

a length of wire coupled around at least part of said portion of the body of said patient; and

Applicants : Morris et al. September 7, 2007 Serial No. : 10/798,100 Dkt. No. 73269/5

Page 4 of 13

means for measuring a voltage developed on said length of wire in a magnetic field, said means for measuring a voltage positioned within said magnetic field and having a first input connected to said and an output representing the motion of said portion of the body of said patient.

7. (Previously Presented) An apparatus for measuring motion of a portion of the body of a patient and an electrocardiogram of a patient in a magnetic field, comprising:

first and second ECG electrodes attached to said patient;

first and second ECG leads connected respectively to said first and second electrodes, one of said ECG leads enclosing at least part of said portion of the body of said patient; and

a voltage measuring device having an input coupled to said ECG leads and an output representing the motion of the body of said patient and the electrocardiogram of said patient.

- 8. (Previously Presented) The apparatus of Claim 7, further comprising a cradle coupled around at least part of said portion of the body of said patient and coupled to said one of said ECG leads enclosing at least part of said portion of the body of said patient.
- 9. (Original) The apparatus of Claim 8, wherein said cradle is formed from a thin polycarbonate plastic strip.
- 10. (Previously Presented) The apparatus of Claim 7, wherein said ECG leads are formed from high resistance leads.
- 11. (Previously Presented) The apparatus of Claim 7, wherein said voltage measuring device comprises:

a Faraday shield forming an enclosure;

two RF filters mounted in said Faraday shield, each of said RF filters having an input coupled to a respective one of said ECG leads and an output;

a differential amplifier mounted within said enclosure and having two inputs and an output, each of said inputs coupled to a respective output of one of said two RF filters;

a gradient filter mounted within said enclosure and having an input and an output, said input of said gradient filter coupled to said output of said differential amplifier, and

a transmitter mounted within said enclosure and having an input coupled to said output of said gradient filter and an output representative of the motion of said portion of the body of said patient.

12. (Previously Presented) The apparatus of Claim 7, wherein said voltage measuring device comprises:

a Faraday shield forming an enclosure and coupled to a first one of said ECG leads;

an RF filter mounted in said Faraday shield having an input coupled to a second one of said ECG leads and an output;

a differential amplifier mounted within said enclosure and having two inputs and an output, one of said inputs coupled to said output of said RF filter and the other of said inputs connected to said Faraday shield;

a gradient filter mounted within said enclosure and having an input and an output, said input of said gradient filter coupled to said output of said differential amplifier, and

a transmitter mounted within said enclosure and having an input coupled to said output of said gradient filter and an output representative of the motion of said portion of the body of said patient.

Applicants : Morris et al. Serial No. : 10/798,100

Page 6 of 13

13. (Previously Presented) A method for measuring motion of a portion of the body of a patient in a magnetic field, comprising:

coupling a cradle to at least part of said portion of the body of said patient; coupling a length of wire to said cradle; and

measuring the voltage developed on said length of wire to generate a signal representing the motion of said portion of the body of said patient.

- 14. (Original) The method of Claim 13, wherein said cradle is formed from a thin polycarbonate plastic strip.
- 15. (Original) The method of Claim 13, wherein said length of wire is formed from a high resistance lead.
- 16. (Previously Presented) A method for measuring motion of a portion of the body of a patient in a magnetic field, comprising:

positioning a length of wire around at least part of said portion of the body of said patient; and

measuring, within said magnetic field, a voltage developed on said length of wire in a magnetic field to generate a signal representing the motion of said portion of the body of said patient.

17. (Currently Amended) A method for measuring motion of a portion of the body of a patient and an electrocardiogram of a patient in a magnetic field, comprising:

attaching a first ECG electrode and a second ECG electrode to said the patient; connecting a first ECG lead to said first ECG electrode at a first end thereof;

Morris et al. Serial No. : 10/798,100 Page 7 of 13

connecting a second ECG lead to said second ECG electrode at a first end thereof;

coupling said second ECG lead around at least part of said the portion of the body of said the patient; and

measuring a voltage developed between a second end of said first ECG lead and a second end of said second ECG lead to generate a signal representing the motion of said the portion of the body of said the patient and the electrocardiogram of said the patient.

- 18. (Currently Amended) The method of Claim 17, further comprising the step of positioning a cradle attached around at least part of said the portion of the body of said the patient, said cradle coupled to said second ECG lead.
- 19. (Original) The method of Claim 18, wherein said cradle is formed from a thin polycarbonate plastic strip.
- 20. (Previously Presented) The method of Claim 17, wherein said first ECG lead and said second ECG lead are formed from high resistance leads.
- 21. (Currently Amended) An apparatus for measuring motion of a an exterior portion of the body of a patient in a magnetic field, comprising:

means for detecting motion of said the exterior portion of the body of said the patient; and

a voltage measuring device connected to said detecting means and having an output representing the motion of said the exterior portion of the body of said the patient.

22. (Currently Amended) The apparatus of Claim 21, wherein said means for detecting motion of said the exterior portion of the body of said the patient comprises: Morris et al. September 7, 2007 10/798,100 Dkt. No. 73269/5

Serial No. : Page 8 of 13

Applicants:

a cradle coupled around at least part of said the exterior portion of the body of said the patient;

a length of wire coupled to said cradle and responsive to motion of said the exterior portion of the body of said the patient.

23. (Currently Amended) The apparatus of Claim 21, wherein said means for detecting motion of said the exterior portion of the body of said the patient comprises:

first and second ECG electrodes attached to said the patient; and

first and second ECG leads connected respectively to said first and second electrodes, one of said ECG leads enclosing at least part of said the exterior portion of the body of said the patient.

24. (Previously Presented) An apparatus for measuring motion of a portion of the body of a patient in a magnetic field, comprising:

a cradle adapted to be coupled around at least part of a portion of the body of a patient;

a length of wire coupled to said cradle and, when coupled to a patient, responsive to motion of said portion of the body of said patient; and

a voltage measuring device having an input coupled to said wire and an output representative of the motion of said portion of the body of said patient.

25. (New) An apparatus for measuring respiration of a patient in a magnetic field, comprising:

first and second ECG electrodes attached to the patient;

Applicants :

Morris et al.

Serial No. :

10/798,100

Page 9 of 13

September 7, 2007 Dkt. No. 73269/5

first and second ECG leads connected respectively to said first and second electrodes, one of said ECG leads enclosing at least part of a portion of the body of the patient; and

a voltage measuring device connected to first and second ECG leads and having an output representing the respiration of the patient and the electrocardiogram of the patient.